

FILT'RAY Compact 2-month faucet and wall-mounted filter

Ref. AT20250US

Sterile



DESCRIPTION

FILT'RAY Compact 2-month faucet and wall-mounted filter
Ref. AT20250US

AQUATOOLS anti-Legionella and all-germ faucet and shower head filter, shower flow.

Device material: ABS.

Membrane type: tubular microfiltration.

Membrane material: polyethylene.

Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.

Filtration flow rate: 1.98 gal/min at 43.5 psi and 1.20 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).

Maximum upstream pressure at the point-of-use: 72.5 psi.

Maximum lifespan: 2 months from installation.

Thermal shock resistance: 158°F for 30 minutes.

Chemical shock resistance: active chlorine levels of up to 100 ppm for 3 hours (cumulative total).

Sterile filter.

FILT'RAY Compact sterile disposable water filters are:

CE marked Class Is Medical Devices in Europe that comply with European Regulation EU 2017/745 CE Marking year 2023;

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance.

Box of 10. Each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 2-month faucet and wall-mounted filter - Ref. AT20250US

| | |
|------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Technology | Point-of-use filtration |
| Height | 1.97 in; 50 mm |
| Flow rate | 1.20 gal/min at 14.5 psi, 1.98 gal/min at 43.5 psi and 2.07 gal/min at 72.5 psi. 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar |
| Diameter | 2.2 in; 56 mm |
| Lifespan | 2 months |

ADVANTAGES



Anti-Legionella and all-germ



Space-saving



Optimized position: angled connection



Lifespan: 2 months after installation

