

FILT'RAY Compact 2-month handheld shower filter

Ref. AT20261US

Sterile

DESCRIPTION

FILT'RAY Compact 2-month handheld shower filter **Ref. AT20261US**

AQUATOOLS anti-Legionella and all-germ handheld shower filters, shower flow. Device material: ABS. Membrane type: tubular microfiltration. Membrane material: polyethylene. Molecular weight cut-off: 0.1 μ m nominal and 0.2 μ m absolute sterilizing grade. Filtration flow rate: 2.91 gal/min at 43.5 psi and 1.61 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet). Maximum upstream pressure at the point-of-use: 72.5 psi.

Maximum lifespan: 2 months from installation.

Thermal shock resistance: 158°F for 30 minutes.

Chemical shock resistance: active chlorine levels of up to 100 ppm for 3 hours (cumulative total).

Sterile filter.

FILT'RAY Compact sterile disposable water filters are:

CE marked Class Is Medical Devices in Europe that comply with European Regulation EU 2017/745 CE Marking year 2023;

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance.

Box of 10. Each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 2-month handheld shower filter - Ref. AT20261US

Connector	M1/2"
Technology	Point-of-use filtration
Height	3.03 in; 77 mm
Length	7.64 in; 194 mm
Flow rate	1.61 gal/min at 14.5 psi, 2.91 gal/min at 43.5 psi and 2.90 gal/min at 72.5 psi. 6.2 Ipm at 1 bar, 11.2 Ipm at 3 bar and 13.2 Ipm at 5 bar
Diameter	2.2 in; 56 mm
Lifespan	2 months



ADVANTAGES



Lifespan: 2 months after installation

