

# FILT'RAY Compact 3-month faucet and wall-mounted shower filter

Ref. AT20350US

Sterile



## DESCRIPTION

**FILT'RAY Compact 3-month faucet and wall-mounted shower filter**  
Ref. AT20350US

AQUATOOLS anti-Legionella and all-germ faucet and wall-mounted filter, shower flow.

Device material: ABS.

Membrane type: tubular microfiltration.

Membrane material: polyethylene.

Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.

Filtration flow rate: 1.98 gal/min at 43.5 psi and 1.20 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).

Maximum upstream pressure at the point-of-use: 72.5 psi.

Maximum lifespan: 3 months from installation.

Thermal shock resistance: 158°F for 30 minutes.

Chemical shock resistance: active chlorine levels of up to 100 ppm for 4 hours (cumulative total).

Sterile filter.

FILT'RAY Compact sterile disposable water filters are:

CE marked Class Is Medical Devices in Europe that comply with European Regulation EU 2017/745 CE Marking year 2023;

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance.

Box of 10. Each filter is individually wrapped and sterile.

## TECHNICAL CHARACTERISTICS

**FILT'RAY Compact 3-month faucet and wall-mounted shower filter - Ref. AT20350US**

| Technology | Point-of-use filtration  |
|------------|--|
| Height     | 2.48 in; 63 mm   |
| Flow rate  | 1.20 gal/min at 14.5 psi, 1.98 gal/min at 43.5 psi and 2.07 gal/min at 72.5 psi. 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar |
| Diameter   | 2.2 in; 56 mm  |
| Lifespan   | 3 months   |

## ADVANTAGES



Anti-Legionella and all-germ



Space-saving



Optimized position: angled connection



Lifespan: 3 months after installation

