

FILT'RAY Compact 3-month faucet filter

Ref. AT20351US

Sterile



DESCRIPTION

FILT'RAY Compact 3-month faucet filter
Ref. AT20351US

AQUATOOLS anti-Legionella and all-germ faucet filter, straight flow.
 Device material: ABS.
 Membrane type: tubular microfiltration.
 Membrane material: polyethylene.
 Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.
 Filtration flow rate: 1.98 gal/min at 43.5 psi and 1.20 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).
 Maximum upstream pressure at the point-of-use: 72.5 psi.
 Maximum lifespan: 3 months from installation.
 Thermal shock resistance: 158°F for 30 minutes.
 Chemical shock resistance: active chlorine levels of up to 100 ppm for 4 hours (cumulative total).
 Sterile filter.
 FILT'RAY Compact sterile disposable water filters are:
 CE marked Class Is Medical Devices in Europe that comply with European Regulation EU 2017/745 CE Marking year 2023;
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance.
 Box of 10. Each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 3-month faucet filter - Ref. AT20351US

Technology	Point-of-use filtration
Height	2.48 in; 63 mm
Flow rate	1.01 gal/min at 14.5 psi, 1.67 gal/min at 43.5 psi and 2.07 gal/min at 72.5 psi. 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	2.2 in; 56 mm
Lifespan	3 months

ADVANTAGES



Anti-Legionella and all-germ



Space-saving



Optimized position: angled connection



Lifespan: 3 months after installation

