

FILT'RAY 1-month wall-mounted shower filter

Ref. AT030777

Sterile

DESCRIPTION

FILT'RAY 1-month wall-mounted shower filter

Ref. AT030777

AQUATOOLS anti-Legionella and all-germ shower filter.

Device: ABS.

Membrane type: tubular microfiltration.

Membrane: polyethylene.

Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.

Filtration flow rate: 3.1 gal/min at 43.5 psi and 1.2 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the shower).

Maximum upstream pressure at the point-of-use: 72.5 psi.

Maximum lifespan: 1 month from installation.

Thermal shock resistance: 158°F for 30 minutes.

Chemical shock resistance: active chlorine levels of up to 100 ppm for 1 hour (cumulative total).

Sterile filter.

FILT'RAY sterile disposable water filters are:

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;

Box of 10. Each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY 1-month wall-mounted shower filter - Ref. AT030777

Technology	Point-of-use filtration
Height	2.83 in; 72 mm
Length	2.95 in; 75 mm
Flow rate	1.7 gal/min at 43.5 psi, 0.6 gal/min at 14.5 psi; 6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	1 month

ADVANTAGES



Anti-Legionella and all-germ



Lifespan : 1 month from installation



Bubl'air Wash : longer filter life



Rapid installation with no tools required

